Article Index, January—June, 1973

NOTES: C (Circuit Design Award); F (Design Feature); N (News); P (Progress in Products)

Circuits/Circuit Design

A programmable pulse-edge selector. April 20, pg. 85 (C)

A synchronized phase-locked loop. March 20, pg. 84 (C)

Ac-to-dc converter uses integrated circuits. February 5, pg. 87 (C)

Ac-to-dc converters for low-level input signals. April 5, pg. 60 (F)

Active-filter design using generalized impedance converters. February 5, pg. 68 (F)

A/D and D/A converters: bridging the analog world to the computer. February 5, pg. 24 (F)

An analog multiplier/divider circuit. May 5, pg. 74 (C)

Analog switch and IC amp controls 80V rms. February 20, pg. 91 (C)

Approximate analog functions with a low-cost multiplier/divider. February 5, pg. 50 (F)

Are you getting the most bandwidth from your design? May 5, pg. 52 (F)

Astable operation of IC timers can be improved. June 20, pg. 83 (C)

BASIC program performs lowpass-to-bandpass transformations. January 5, pg. 98 (F)

Battery saver has automatic turn-off. April 20, pg. 91 (C)

Cascade adder improves system speed for high-speed multiply operations. April 20, pg. 74 (F)

Cascaded active circuits yield 90-degree phase-difference networks. April 5, pg. 52 (F)

Choose the right analog multiplier by understanding its limitations. May 5, pg. 66 (F)

Circuit protects power supply regulator from overcurrent. February 5, pg. 89 (C)

Circuit selects larger of two analog signals. April 20, pg. 87 (C)

Circuit shifts asynchronous high-frequency clock sources. January 20, pg. 99 (C)

Clocked square-wave generator uses CMOS. March 5, pg. 85 (C)

CMOS linear-ramp generator has amplitude control. June 20, pg. 87 (C)

Compensated adjustable zener. May 5, pg. 72 (C)

Continuously variable voltage regulator. February 20, pg. 91 (C)

Convert a CMOS gate to a wide-hysteresis Schmitt trigger. January 20, pg. 95 (C)

Convert wrap-around code to sign-plus-magnitude. January 5, pg. 103 (C)

Delta-sigma A/D conversion can save $$ in slow-speed applications. March 20, pg. 78 (F)

Designers Guide to: Charge-coupled devices. January 20, pg. 34 (F)

Designers Guide to: Instrumentation amplifiers. May 5, pg. 40 (F)

Differential-temperature sensor is very inexpensive. April 5, pg. 90 (C)

Differentiator circuit produces a relative change. January 20, pg. 97 (C)

Digital absolute-value circuit. June 20, pg. 85 (C)

Diodes provide switching and isolation for absquare circuit. March 5, pg. 89 (C)

EDN Design Course CMOS-Part V—CMOS gates in linear applications: the results are surprisingly good. March 5, pg. 42 (F)

End edge ambiguities with two ICs. April 5, pg. 88 (C)

Everyone knows that inductive loads can greatly shorten contact life. April 5, pg. 64 (F)

FET probe drives 50Ω load. March 5, pg. 87 (C)

FET stabilizes sine-wave oscillator. June 5, pg. 87 (C)

FETs work well in active balanced mixers. January 5, pg. 66 (F)

Get the most out of log amplifiers by understanding the error sources. January 20, pg. 52 (F)

Getting to know capacitors better with a simple C/V display circuit. March 20, pg. 62 (F)

High-speed, high-resolution A/D converters: Here's how. June 5, pg. 62 (F)

Hysteresis increases versatility of bidirectional one-shot. January 5, pg. 103 (C)

IC timer makes adjustable Schmitt trigger. May 5, pg. 73 (C)

Improve high-power circuit designs with fast-recovery power diodes. April 20, pg. 68 (F)

Integrate and dump circuit uses no power supply. February 20, pg. 93 (C)

Interfacing CMOS with other logic and display devices. February 5, pg. 38 (F)

Isolated current source. April 20, pg. 85 (C)

Lamp test becomes circuit test. February 5, pg. 91 (C)

Leakage testing of diode and JFETs. May 5, pg. 72 (C)

Article Index, January—June, 1973

NOTES: C (Circuit Design Award); F (Design Feature); N (News); P (Progress in Products)

Circuits/Circuit Design

A programmable pulse-edge selector. April 20, pg. 85 (C)

A synchronized phase-locked loop. March 20, pg. 84 (C)

Ac-to-dc converter uses integrated circuits. February 5, pg. 87 (C)

Ac-to-dc converters for low-level input signals. April 5, pg. 60 (F)

Active-filter design using generalized impedance converters. February 5, pg. 68 (F)

A/D and D/A converters: bridging the analog world to the computer. February 5, pg. 24 (F)

An analog multiplier/divider circuit. May 5, pg. 74 (C)

Analog switch and IC amp controls 80V rms. February 20, pg. 91 (C)

Approximate analog functions with a low-cost multiplier/divider. February 5, pg. 50 (F)

Are you getting the most bandwidth from your design? May 5, pg. 52 (F)

Astable operation of IC timers can be improved. June 20, pg. 83 (C)

BASIC program performs lowpass-to-bandpass transformations. January 5, pg. 98 (F)

Battery saver has automatic turn-off. April 20, pg. 91 (C)

Cascade adder improves system speed for high-speed multiply operations. April 20, pg. 74 (F)

Cascaded active circuits yield 90-degree phase-difference networks. April 5, pg. 52 (F)

Choose the right analog multiplier by understanding its limitations. May 5, pg. 66 (F)

Circuit protects power supply regulator from overcurrent. February 5, pg. 89 (C)

Circuit selects larger of two analog signals. April 20, pg. 87 (C)

Circuit shifts asynchronous high-frequency clock sources. January 20, pg. 99 (C)

Clocked square-wave generator uses CMOS. March 5, pg. 85 (C)

CMOS linear-ramp generator has amplitude control. June 20, pg. 87 (C)

Compensated adjustable zener. May 5, pg. 72 (C)

Continuously variable voltage regulator. February 20, pg. 91 (C)

Convert a CMOS gate to a wide-hysteresis Schmitt trigger. January 20, pg. 95 (C)

Convert wrap-around code to sign-plus-magnitude. January 5, pg. 103 (C)

Delta-sigma A/D conversion can save $$ in slow-speed applications. March 20, pg. 78 (F)

Designers Guide to: Charge-coupled devices. January 20, pg. 34 (F)

Designers Guide to: Instrumentation amplifiers. May 5, pg. 40 (F)

Differential-temperature sensor is very inexpensive. April 5, pg. 90 (C)

Differentiator circuit produces a relative change. January 20, pg. 97 (C)

Digital absolute-value circuit. June 20, pg. 85 (C)

Diodes provide switching and isolation for absquare circuit. March 5, pg. 89 (C)

EDN Design Course CMOS-Part V—CMOS gates in linear applications: the results are surprisingly good. March 5, pg. 42 (F)

End edge ambiguities with two ICs. April 5, pg. 88 (C)

Everyone knows that inductive loads can greatly shorten contact life. April 5, pg. 64 (F)

FET probe drives 50Ω load. March 5, pg. 87 (C)

FET stabilizes sine-wave oscillator. June 5, pg. 87 (C)

FETs work well in active balanced mixers. January 5, pg. 66 (F)

Get the most out of log amplifiers by understanding the error sources. January 20, pg. 52 (F)

Getting to know capacitors better with a simple C/V display circuit. March 20, pg. 62 (F)

High-speed, high-resolution A/D converters: Here's how. June 5, pg. 62 (F)

Hysteresis increases versatility of bidirectional one-shot. January 5, pg. 103 (C)

IC timer makes adjustable Schmitt trigger. May 5, pg. 73 (C)

Improve high-power circuit designs with fast-recovery power diodes. April 20, pg. 68 (F)

Integrate and dump circuit uses no power supply. February 20, pg. 93 (C)

Interfacing CMOS with other logic and display devices. February 5, pg. 38 (F)

Isolated current source. April 20, pg. 85 (C)

Lamp test becomes circuit test. February 5, pg. 91 (C)

Leakage testing of diode and JFETs. May 5, pg. 72 (C)

Low-cost charge amplifier. May 20, pg. 83 (C)

Make exceptionally stable and linear light measurements. February 5, pg. 86 (C)

Make sure your logic keeps pace with memory cycle times. January 20, pg. 70 (F)

More bits/chip leads to economical semiconductor-memory systems. February 20, pg. 76 (F)

Multiplexers synthesize Boolean expressions. June 5, pg. 87 (C)

Op amp in active filter can also provide gain. February 5, pg. 91 (C)

Optical sensor has built-in hysteresis. June 5, pg. 91 (C)

Opto isolators provide foldover indication. April 5, pg. 91 (C)

Peak holder stretches narrow video pulses. February 5, pg. 46 (F)

Phase-locked loop stereo decoder is aligned easily. January 20, pg. 95 (C)

Phase-shifter for phase-locked loops. March 20, pg. 86 (C)

Poor man's LED driver is TTL compatible. February 5, pg. 86 (C)

Positive feedback "idealizes" small transformers. June 5, pg. 85 (C)

Power distribution and regulation can be simple, cheap and rugged. February 20, pg. 52 (F)

Power-supply modification turns standard calculator chip into unique product. April 20, pg. 25 (N)

Pulse catcher uses two ICs. January 5, pg. 109 (C)

Put the IC timer to work in a myriad of ways. March 5, pg. 54 (F)

Ramp generator has adjustable nonlinearity. May 20, pg. 85 (C)

Real-time 7-segment to BCD converter. June 20, pg. 89 (C)

Self-clearing digital sequence detector. April 5, pg. 88 (C)

Set-reset latch uses optical couplers. January 5, pg. 107 (C)

7-segment to BCD decoder. February 20, pg. 92 (C)

Simple electronic timer is compact and accurate. April 20, pg. 89 (C)

Simple ±15V regulated supply provides tracking. March 20, pg. 87 (C)

600V switching circuit provides good speed and isolation. February 20, pg. 90 (C)

Successive approximation registers: fast, powerful building blocks. February 20, pg. 24 (F)

Tailor the response of your active filters. March 5, pg. 68 (F)

Take the guesswork out of phase-locked loop design. January 5, pg. 54 (F)

Texas engineer wins 1st prize in EDN's 1973 Creative Design Contest. June 5, pg. 52 (F)

The basics of using FETs for analog-signal switching. May 20, pg. 56 (F)

Three ICs monitor pulse width. March 20, pg. 86 (C)

Three-phase A/D conversion has high accuracy and low cost. January 20, pg. 82 (F)

Totally implantable heart depends heavily on electronics for timing and control. January 20, pg. 14 (N)

Trilogic, a three-level logic system provides greater memory density. April 20, pg. 80 (F)

True rms measurements using IC multipliers. March 20, pg. 85 (C)

Two gates make quartz oscillator. May 5, pg. 74 (C)

Use decimal CORDIC for generation of many transcendental functions. February 20, pg. 64 (F)

Use integrated circuits in transformerless dc-to-dc converter. February 5, pg. 58 (F)

Use opto-isolation in your next video amp. March 5, pg. 91 (C)

Variable limit switch permits hands-off equipment cycling. January 20, pg. 66 (F)

When the voltage drops, new TV receivers keep right on operating. February 20, pg. 20 (N)

Wide-range pulse generator uses single IC. January 5, pg. 107 (C)

Window detector uses one IC regulator. May 20, pg. 81 (C)

Yes, the noisy transistor-switching regulator can be quieted. February 5, pg. 54 (F)

You can get expert help with your designs if you know where to look. March 20, pg. 50 (F)

Communications

Are you getting the most bandwidth from your design? May 5, pg. 52 (F)

Canadian digital-data communications system offers users dramatic savings. May 5, pg. 24 (N)

Communication circuits: Putting data on the telephone network. June 5, pg. 30 (F)

Compact instrument allows simulation of phone-line impairments in the laboratory. June 20, pg. 90 (P)

Digital filters: the best way to go once improvements in ICs make the price right. February 20, pg. 14 (N)

Ease radio-spectrum congestion by bandwidth compression/expansion. May 20, pg. 74 (F)

Minicomputers relieve big brothers of data-communication chores. May 20, pg. 32 (F)

1973 NCC focuses on total spectrum of computer technology. May 20, pg. 46 (F)

Short-haul infrared link connects rem te terminal to computer. February 20, pg. 19 (N)

Components/Modules

An advancement in Ni-Cd battery technology: recharging in as little as 15 minutes. June 20, pg. 28 (N)

April 1 Special—New components simplify electronic circuitry. April 5, pg. 80 (F)

Chose the right analog multiplier by understanding its limitations. May 5, pg. 66 (F)

Dc-to-dc converter family feature triple outputs and low-thermal impedance. March 20, pg. 89 (P)

Designers discuss IC op amps: are they as good as they should be? January 20, pg. 90 (F)

Designers Guide to: Fractional-horsepower motors—Part 1. March 20, pg. 68 (F)

Designers Guide to: Fractional-horsepower motors—Part 2. April 5, pg. 74 (F)

Designers Guide to: Instrumentation amplifiers. May 5, pg. 40 (F)

840W power supply has 50 to 260V ac input range. June 20, pg. 91 (P)

5V, 10A regulated power supply comes in 2-in. cube and sells for $99. February 20, pg. 95 (P)

Force-Switchable Diodes (FSDs) offer possibilities for low-cost solid-state switching. March 20, pg. 18 (N)

Getting to know capacitors better with a simple C/V display circuit. March 20, pg. 62 (F)

Guidelines for selecting linear solenoids. May 5, pg. 30 (F)

Guidelines for the selection of potentiometers. June 20, pg. 62 (F)

IEEE Intercon '73: "Solid State Shapes The Future". March 20, pg. 36 (F)

Low-cost 4-1/2-digit DPM with LED display operates from 5V dc. January 5, pg. 111 (P)

Miniature 12-bit D/A and A/Ds are guaranteed stable to ±1/2-LSB linearity over full mil-temp range. May 20, pg. 89 (P)

Monolithic multiplier/divider requires no external trimming. April 5, pg. 93 (P)

New ceramics can be used as control or switching elements. June 5, pg. 25 (N)

Positive feedback "idealizes" small transformers. June 5, pg. 85 (C)

Potentiometer operates in 1000°F environment. February 20, pg. 17 (N)

Relay conference provides valuable info for users and manufacturers alike. June 20, pg. 31 (N)

Rms-to-dc converter module rivals bench instrument performance. March 5, pg. 94 (P)

Size and price breakthrough in sample-and-hold amplifiers, a 1.4×0.6×0.4-in. unit for only $29 in singles. January 5, pg. 115 (P)

Socket your ICs and save money in the process. February 20, pg. 44 (F)

Solid-state relays switch 10A and feature zero-crossing turn-on and turn-off. February 5, pg. 93 (P)

Study results should yield better laser-trimmed thin-film resistors. June 5, pg. 26 (N)

Take another look at resonant-reed relays. June 20, pg. 74 (F)

Take the guesswork out of phase-locked loop design. January 5, pg. 54 (F)

The impact of bulk alloys on resistor technology. June 5, pg. 78 (F)

Computers/ Data Processing

Advanced laser scanning system extends single-channel bandwidth beyond 100 MHz. June 20, pg. 29 (N)

Air Force to receive operational bubble memory. January 5, pg. 17 (N)

BASIC program performs lowpass-to-bandpass transformations. January 5, pg. 98 (F)

Communication circuits: Putting data on the telephone network. June 5, pg. 30 (F)

Designers Roundtable—Users and designers discuss interactive computer terminals. June 20, pg. 78 (F)

Dynamic RAM elements can yield static RAM systems. June 20, pg. 46 (F)

Electronic response system promotes student-teacher communications. March 5, pg. 20 (N)

Hewlett-Packard's HP-35 calculator has a brother. One for the financial market. March 5, pg. 21 (N)

High-density holographic memory system provides high-quality images. May 5, pg. 26 (N)

IEEE Intercon '73: "Solid State Shapes The Future". March 20, pg. 36 (F)

Lamp filament material shrinks computer memory and cuts power. June 5, pg. 22 (N)

LSI computer-on-card will be basic digital building block. June 20, pg. 26 (N)

Make sure your logic keeps pace with memory cycle times. January 20, pg. 70 (F)

Minicomputers relieve big brothers of data communication chores. May 20, pg. 32 (F)

More bits/chip leads to economical semiconductor memory systems. February 20, pg. 76 (F)

Multiplexers synthesize Boolean expressions. June 5, pg. 87 (C)

New display technique presents data in 4-dimensional patterns. June 5, pg. 23 (N)

New printing technology debuts in high-speed line printer. January 5, pg. 20 (N)

New, single-module, programmable computer has 2k memory. May 5, pg. 23 (N)

1973 NCC focuses on total spectrum of computer technology. May 20, pg. 46 (F)

Programmable ROMs expand in power density and speed. January 5, pg. 16 (N)

Punched-tape reader uses ac drive to cut data-entry cost by 50%. February 5, pg. 92 (P)

Save ROMs in high-resolution dot-matrix displays and printers. May 5, pg. 56 (F)

Short-haul infrared link connects remote terminal to computer. February 20, pg. 19 (N)

16-bit LSI minicomputer could open up new application areas. May 5, pg. 78 (P)

The hybrid digital computer: A new architectural approach. June 20, pg. 56 (F)

Trilogic, a three-level logic system provides greater memory density. April 20, pg. 80 (F)

Use decimal CORDIC for generation of many transcendental functions. February 20, pg. 64 (F)

Displays

Automated-graphics system takes the drudgery out of drafting. April 20, pg. 26 (N)

Channel display uses MOS/LSI. April 20, pg. 24 (N)

Data-sheet dialogue—Reader's responses to DPM data sheets: More details—less specsmanship! May 5, pg. 46 (F)

Designers Roundtable—Users and designers discuss interactive computer terminals. June 20, pg. 78 (F)

Four-quadrant multiplying D/A converter minimizes spiking and feedthrough. June 5, pg. 93 (P)

High-density holographic memory system provides high-quality images. May 5, pg. 26 (N)

IC drivers offer a systems approach for multiplexed high-voltage displays. June 5, pg. 92 (P)

Liquid-crystal light valve acts as image intensifier. February 5, pg. 17 (N)

Magnetic storage system for full-color video display developed for maps and other avionic readouts. April 20, pg. 27 (N)

New display technique presents data in 4-dimensional patterns. June 5, pg. 23 (N)

Progress in CCDs and photosensitive devices stirs interest at ISSCC. April 5, pg. 20 (N)

Real-time 7-segment to BCD converter. June 20, pg. 89 (C)

Save ROMs in high-resolution dot-matrix displays and printers. May 5, pg. 56 (F)

What do you know about selecting an LED readout? January 20, pg. 60 (F)

When the voltage drops, new TV receivers keep right on operating. February 20, pg. 20 (N)

Instrumentation

Automatic test equipment: users report on interface problems. June 5, pg. 27 (N)

Comparing static inverters for uninterruptible ac power system. January 5, pg. 86 (F)

Data acquisition costs less with DMM/calculator pair. May 20, pg. 88 (P)

Designers Guide to: Instrumentation amplifiers. May 5, pg. 40 (F)

Designers Roundtable—How users look at bench test equipment and its manufacturers. March 5, pg. 32 (F)

Digital-processing interface ties the scope to the computer. May 5, pg. 81 (P)

Digital storage techniques used in medical pulse analyzer. May 20, pg. 20 (N)

Electron microscopes move "on line" at semiconductor manufacturers. March 5, pg. 14 (N)

Fully automatic 4-digit portable multimeter uses triple-slope integration. January 5, pg. 110 (P)

Have you kept up with sampling scopes? May 20, pg. 66 (F)

Hewlett-Packard's HP-35 calculator has a brother. One for the financial market. March 5, pg. 21 (N)

IEEE Intercon '73: "Solid State Shapes The Future". March 20, pg. 36 (F)

Light scanner on Skylab to aid in study of Earth resources. February 5, pg. 14 (N)

Logic analyzer instrument adds a new dimension for viewing complex digital signals. June 5, pg. 94 (P)

New printing technology debuts in high-speed line printer. January 5, pg. 20 (N)

Sensors monitor earth tilt to detect earthquakes. January 5, pg. 19 (N)

Study results should yield better laser-trimmed thin-film resistors. June 5, pg. 26 (N)

The function generator: more flexibility at lower prices. April 20, pg. 36 (F)

True 3.5-digit DMM gives 5000-count resolution for 2000-count prices. April 20, pg. 95 (P)

Ultraviolet light removes excess photoresist—speeds SC fabrication. January 20, pg. 20 (N)

Versatility and flexibility characterize 4-channel transient recorder. April 20, pg. 94 (P)

Management/Interface

An engineer's guide to configuration management. February 5, pg. 78 (F)

Field service can be a valuable design tool if properly used. June 20, pg. 68 (F)

Diode laser inventor issues warning of lagging US R&D funds. April 5, pg. 25 (N)

EIA figures point to 1972 electronics industry volume of $29.8 billion. February 5, pg. 16 (N)

Gene Carter of National Semiconductor speaks out on the pROM as a design tool. March 5, pg. 76 (F)

How to write technical articles, and why you'll be glad you did. April 20, pg. 60 (F)

Keep up with the latest in engineering information. January 20, pg. 44 (F)

Meet the editors—and learn how to write for publication. April 20, pg. 24 (N)

The broad scope of solid-state technology. January 5, pg. 38 (F)

You can get expert help with your designs if you know where to look. March 20, pg. 50 (F)

Materials

Everyone knows that inductive loads can greatly shorten contact life. April 5, pg. 64 (F)

Force-Switchable Diodes (FSDs) offer possibilities for low-cost solid-state switching. March 20, pg. 18 (N)

Get better price/performance from electrical contacts. June 5, pg. 72 (F)

Ion implantation reduces resistor areas in ICs. February 5, pg. 14 (N)

Lamp filament material shrinks computer memory and cuts power. June 5, pg. 22 (N)

Magnetic-levitation train relies on cryogenics for high-speed transport. May 5, pg. 24 (N)

Metallization process promises low-cost continuous-strip, flexible ICs. April 5, pg. 23 (N)

Mylar disc stores video programming for TV viewers. February 5, pg. 16 (N)

New ceramics can be used as control or switching elements. June 5, pg. 25 (F)

The impact of bulk alloys on resistor technology. June 5, pg. 78 (F)

Ultraviolet light removes excess photoresist—speeds SC fabrication. January 20, pg. 20 (N)

Water-soluble paper speeds assembly of printed circuit boards. January 20, pg. 104 (P)

Packaging

Detect faulty IC die bonds using voltage measurements. February 20, pg. 48 (F)

5V, 10A regulated power supply comes in 2-in. cube and sells for $99. February 20, pg. 95 (P)

Metallization process promises low-cost continuous-strip, flexible ICs. April 5, pg. 23 (N)

Mylar disc stores video programming for TV viewers. February 5, pg. 16 (N)

New, single-module, programmable computer has 2k memory. May 5, pg. 23 (N)

Socket your ICs and save money in the process. February 20, pg. 44 (F)

Water-soluble paper speeds assembly of printed circuit boards. January 20, pg. 104 (P)

What do you know about selecting an LED readout? January 20, pg. 60 (F)

Three-dimensional packaging to challenge printed circuit boards. January 5, pg. 17 (N)

Semiconductors

Ac-to-dc converter uses integrated circuits. February 5, pg. 87 (C)

Ac-to-dc converters for low-level input signals. April 5, pg. 60 (F)

Analog switch and IC amp controls 80V rms. February 20, pg. 91 (C)

Approximate analog functions with a low-cost multiplier/divider. February 5, pg. 50 (F)

Cascade adder improves system speed for high-speed multiply operations. April 20, pg. 74 (F)

Choose the right analog multiplier by understanding its limitations. May 5, pg. 66 (F)

Circuit protects power supply regulator from overcurrent. February 5, pg. 89 (C)

Clocked square-wave generator uses CMOS. March 5, pg. 85 (C)

CMOS—Part VI—Here's a list of manufacturers, their product lines and bibliography. April 20, pg. 48 (F)

Compensated adjustable zener. May 5, pg. 72 (C)

Continuously-variable voltage regulator. February 20, pg. 91 (C)

Convert a CMOS gate to a wide-hysteresis Schmitt trigger. January 20, pg. 95 (C)

Designers discuss IC op amps: are they as good as they should be? January 20, pg. 90 (F)

Designers Guide to: Charge-coupled devices. January 20, pg. 34 (F)

Diodes provide switching and isolation for absquare circuit. March 5, pg. 89 (C)

Dual, TTL-output voltage comparator combines high-speed and excellent input characteristics. January 20, pg. 102 (P)

Dynamic RAM elements can yield static RAM systems. June 20, pg. 46 (F)

EDN Design Course—CMOS—Part V—CMOS gates in linear applications: the results are surprisingly good. March 5, pg. 42 (F)

End edge ambiguities with two ICs. April 5, pg. 88 (C)

FET probe drives 50Ω load. March 5, pg. 87 (C)

FET stabilizes sine-wave oscillator. June 5, pg. 87 (C)

FETs work well in active balanced mixers. January 5, pg. 66 (F)

First full-function ECL counters operate at 100 MHz. January 5, pg. 113 (P)

Four-quadrant multiplying D/A converter minimizes spiking and feedthrough. June 5, pg. 93 (P)

14-bit D/A converter family smashes price barriers: from $85 to $179 in singles! February 20, pg. 96 (P)

Gene Carter of National Semiconductor speaks out on the pROM as a design tool. March 5, pg. 76 (F)

Get the most out of log amplifiers by understanding the error sources. January 20, pg. 52 (F)

IC drivers offer a systems approach for multiplexed high-voltage displays. June 5, pg. 92 (P)

IC dual-tracking regulators prove to be popular items yet few devices are interchangeable for second sourcing. March 5, pg. 16 (N)

IEEE Intercon '73: "Solid State Shapes The Future." March 20, pg. 36 (F)

Improve high-power circuit designs with fast-recovery power diodes. April 20, pg. 68 (F)

Interfacing CMOS with other logic and display devices. February 5, pg. 38 (F)

Ion implantation reduces resistor areas in ICs. February 5, pg. 14 (N)

Leapfrog ahead with standard-family MSI/LSI. April 5, pg. 30 (F)

Low-cost adjustable TO-8 S/H amplifier is versatile. March 20, pg. 89 (P)

LSI in consumer applications, Round 2: clocks on a chip. May 5, pg. 22 (N)

Miniature 12-bit D/A and A/Ds are guaranteed stable to ±1/2-LSB linearity over full mil-temp. range. May 20, pg. 89 (P)

Negative voltage regulation made easy by new 3-terminal device. February 5, pg. 92 (P)

New, single-module, programmable computer has 2k memory. May 5, pg. 23 (N)

Nine more MSI devices in CMOS 4000 Family. February 20, pg. 94 (P)

Op amp in active filter can also provide gain. February 5, pg. 91 (C)

Optical sensor has built-in hysteresis. June 5, pg. 91 (C)

Opto isolators provide foldover indication. April 5, pg. 91 (C)

Power SCs—the big world of fast switching and acres of silicon. June 20, pg. 36 (F)

Programmable ROMs expand in power density and speed. January 5, pg. 16 (N)

Progress in CCDs and photosensitive devices stirs interest at ISSCC. April 5, pg. 20 (N)

Pulse catcher uses two ICs. January 5, pg. 109 (C)

Put the IC timer to work in a myriad of ways. March 5, pg. 54 (F)

Set-reset latch uses optical couplers. January 5, pg. 107 (C)

Simplified methods characterize optical couplers. March 5, pg. 62 (F)

16-bit resolution D/A converters cost only $89. June 5, pg. 94 (P)

Size and price breakthrough in sample-&-hold amplifiers, a 1.4×0.6×0.4-in. unit for only $29 in singles. January 5, pg. 115 (P)

Stan Harris of Analog Devices speaks out on the real world of the 741. June 5, pg. 68 (F)

Successive approximation registers: fast, powerful building blocks. February 20, pg. 24 (F)

Take the guesswork out of phase-locked loop design. January 5, pg. 54 (F)

The basics of using FETs for analog-signal switching. May 20, pg. 56 (F)

The broad scope of solid-state technology. January 5, pg. 38 (F)

The quad 741 op amp is here in a 14-pin DIP. January 20, pg. 103 (P)

Three ICs monitor pulse width. March 20, pg. 86 (C)

Today's hardest design decision: An overview of custom CMOS/LSI. June 5, pg. 42 (F)

20th ISSCC provides exciting glimpses of future LSI devices. March 20, pg. 20 (N)

Unraveling the mysteries of photoelectronic devices. February 20, pg. 34 (F)

Use integrated circuits in transformerless dc-to-dc converter. February 5, pg. 58 (F)

Using CMOS in system designs, those all-important details. January 5, pg. 76 (F)

Yes, the noisy transistor switching regulator can be quieted. February 5, pg. 54 (P)

Systems

A/D and D/A converters: bridging the analog world to the computer. February 5, pg. 24 (F)

Air Force to receive operational bubble memory. January 5, pg. 17 (N)

Automated-graphics system takes the drudgery out of drafting. April 20, pg. 26 (N)

Communication circuits: Putting data on the telephone network. June 5, pg. 30 (F)

Comparing static inverters for uninterruptible ac power systems. January 5, pg. 86 (F)

Designers Guide to: Instrumentation amplifiers. May 5, pg. 40 (F)

Designers Roundtable—Users discuss power supplies from an applications viewpoint. April 5, pg. 44 (F)

Digital filters: the best way to go once improvements in ICs make the price right. February 20, pg. 14 (N)

Dynamic RAM elements can yield static RAM systems. June 20, pg. 46 (F)

Ease radio-spectrum congestion by bandwidth compression/expansion. May 20, pg. 74 (F)

840W power supply has 50 to 260V ac input range. June 20, pg. 91 (P)

Electronic response system promotes student-teacher communications. March 5, pg. 20 (N)

High-speed, high-resolution A/D converters: Here's how. June 5, pg. 62 (F)

Leapfrog ahead with standard-family MSI/LSI. April 5, pg. 30 (F)

LSI computer-on-card will be basic digital building block. June 20, pg. 26 (N)

Magnetic storage system for full-color video display developed for maps and other avionic readouts. April 20, pg. 27 (N)

Measurement breakthrough leads to new value for speed of light. January 20, pg. 16 (N)

More bits/chip leads to economical semiconductor memory systems. February 20, pg. 76 (F)

New, single-module, programmable computer has 2k memory. May 5, pg. 23 (N)

Peak holder stretches narrow video pulses. February 5, pg. 46 (F)

Power distribution and regulation can be simple, cheap and rugged. February 20, pg. 52 (F)

Put the IC timer to work in a myriad of ways. March 5, pg. 54 (F)

Save ROMs in high-resolution dot-matrix displays and printers. May 5, pg. 56 (F)

Successive approximation registers: fast, powerful building blocks. February 20, pg. 24 (F)

Technique uses LSI to speed addition and multiplication in computers. January 20, pg. 15 (N)

The hybrid digital computer: A new architectural approach. June 20, pg. 56 (F)

Totally implantable heart depends heavily on electronics for timing and control. January 20, pg. 14 (N)

Today's hardest design decision: An overview of custom CMOS/LSI. June 5, pg. 42 (F)

Using CMOS in system designs, those all-important details. January 5, pg. 76 (F)

Variable limit switch permits hands-off equipment cycling. January 20, pg. 66 (F)

Test & Measurements

Automatic test equipment: users report on interface problems. June 5, pg. 27 (N)

Compact instrument allows simulation of phone-line impairments in the laboratory. June 20, pg. 90 (P)

Data acquisition costs less with DMM/calculator pair. May 20, pg. 88 (P)

Designers Roundtable—How users look at bench test equipment and its manufacturers. March 5, pg. 32 (F)

Detect faulty IC die bonds using voltage measurements. February 20, pg. 48 (F)

Digital processing interface ties the scope to the computer. May 5, pg. 81 (P)

Digital storage techniques used in medical pulse analyzer. May 20, pg. 20 (N)

Electron microscopes move "on line" at semiconductor manufacturers. March 5, pg. 14 (N)

Fully automatic 4-digit portable multimeter uses triple-slope integration. January 5, pg. 110 (P)

Have you kept up with sampling scopes? May 20, pg. 66 (F)

Lamp test becomes circuit test. February 5, pg. 91 (C)

Leakage testing of diode and JFETs. May 5, pg. 72 (C)

Light scanner on Skylab to aid in study of Earth resources. February 5, pg. 14 (N)

Little-known rules for custom-circuit testing. April 5, pg. 82 (F)

Logic analyzer instrument adds a new dimension for viewing complex digital signals. June 5, pg. 94 (P)

Measurement breakthrough leads to new value for speed of light. January 20, pg. 16 (N)

Sensors monitor earth tilt to detect earthquakes. January 5, pg. 19 (N)

Simplified methods characterize optical couplers. March 5, pg. 62 (F)

The function generator: more flexibility at lower prices. April 20, pg. 36 (F)

True 3.5-digit DMM gives 5000-count resolution for 2000-count prices. April 20, pg. 95 (P)

Versatility and flexibility characterize 4-channel transient recorder. April 20, pg. 94 (P)